

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
43.00	Stream, 1 lk. wide, c NE.	-50
53.50	Spur, c NE.; descend.	+200
58.75	Stream, 5 lks. wide, c N.60°E.	-200
80.06	The cor. to secs. 8, 9, 16 & 17.	

Oct. 16, 1891.

N.0°3'W., on a true line, bet. secs. 8 & 9.

Va.21°10'E.

.75	Spur, c N.80°E.; descend.	+10
7.00	Canyon, c E.; ascend.	-75
9.75	Spur, c E.; descend.	+40
12.25	Canyon, c S.75°E.	-60
17.00	A fir, 48 ins. dia., marked with 2 notches on N. & S. sides.	+200
24.00	Spur, c N.65°E.; thence along E. slope.	+200
38.00	Spur, c N.10°E.	
40.00	This point falling on edge of a bluff of rock, 40 ft. wide, 7 ft. high, with a course N.46°E., I mark a cross (x) at exact spot for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 12 ins. dia., bears N.26°E., 10 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 20 ins. dia., bears S.40°W., 18 lks. dist., marked $\frac{1}{4}$ S B T. Thence along W. slope.	
44.15	A fir, 7 ft. dia., on line, marked with 2 notches on N. & S. sides.	
59.00	Stream, 2 lks. wide, c NE.	-400
65.50	Spur, c N.75°E.; descend.	+100
71.00	Stream, 5 lks. wide, c E.	-150
80.00	Set post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for cor. to secs. 4, 5, 8 & 9, marked T 20 S 4 on NE., R 7 W S 9 on SE., S 8 on SW., S 5 on NW. faces, with 5 notches on S. and 4 notches on E. edges; from which	