

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
8.00	Spur, c N.70°E.; descend.	+100
9.50	A fir, 36 ins. dia., on line, with 2 notches on N. & S. sides.	
17.50	Stream, 2 lks. wide, c S.80°E., with bottom 2 chs.wide.	-250
34.35	A fir, 24 ins. dia., on line, with 2 notches on N. & S. sides.	
	Ascend brushy ridge.	+200
40.00	Set a post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{2}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which	
	A fir, 30 ins. dia., bears N.52°E., 38 lks. dist., marked $\frac{1}{4}$ S B T.	
	A fir, 36 ins. dia., bears S.88°W., 16 lks. dist., marked $\frac{1}{4}$ S B T.	
45.70	Spur, c N.70°E.; descend E. slope.	+80
63.50	Descend abruptly.	
66.00	Canyon, c E.	-300
67.00	Fir, 65 ins. dia., with 2 notches on N. & S. sides.	
75.75	Spur, c SE.	+250
80.00	A leaning fir, 70 ins. dia., on line, with 2 notches on N. & S. sides.	
85.00	Canyon, c SE.; ascend.	-75
85.75	A fir, 40 ins. dia., on line, with 2 notches on N. & S. sides.	
95.50	Top of divide, c E. & W.	+200
96.50	Intersect N. bdy. of township, 8.85 chs. W. of the cor. to secs. 32 & 33, and at said point of intersection I set a sandstone, 18x10x8 ins., 12 ins. in the ground, for closing cor. to secs. 4 & 5, marked C C with 4 notches on E. & 2 notches on W. faces; from which	
	A fir, 48 ins. dia., bears S.70°E., 100 lks. dist., marked T 20 S R 7 W S 4 B T.	
	A fir, 60 ins. dia., bears S.8°W., 43 lks. dist., marked T 20 S R 7 W S 5 B T.	
	A fir, 55 ins. dia., bears N.24°E., 74 lks. dist.,	