

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
79.90	Intersect N. & S. line, 35 lks. S. of cor. to secs. 28, 29, 32 & 33. Thence I run S.89°15'W., on a true line, bet. secs. 29 & 32. Va.21°15'E.	
4.50	Spur, c SW.	+75
14.90	Canyon filled by slide, 3 chs. across, c SE., with stream, 8 lks. wide.	-125
22.90	Spur, c E.	+200
39.95	Set post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 16 ins. dia., bears N.30°E., 10 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 16 ins. dia., bears S.4°W., 20 lks. dist., marked $\frac{1}{4}$ S B T.	-100
65.90	Canyon with slide, 4 chs. wide filling canyon; stream, 4 lks. wide, c SE.; ascend.	-100
79.90	The cor. to secs. 29, 30, 31 & 32. Sept. 12, 1891.	
	S.89°45'W., on a true line, bet. secs. 30 & 31, parallel to the S. bdy. of Sec. 31. Va.21°15'E.	
	Cross canyon, c W., near mouth, 1 ch. wide; ascend ridge.	
3.00	A fir on line, 60 ins. dia., with 2 notches on E. & W. sides. Thence along N. slope.	+75
21.50	Canyon, c N.60°E.; ascend S. slope.	-50
26.50	Fir, 96 ins. dia., on line, with 2 notches on N. & S. sides.	
40.00	Marked a sandstone in place, showing face 20x12 ins., 4 ins. above ground, marked $\frac{1}{4}$ S with cross (x) at exact spot for $\frac{1}{4}$ sec. cor.; from which A fir, 10 ins. dia., bears S.27°E., 25 lks. dist.,	