

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

marked  $\frac{1}{4}$  S. B T.

A fir, 10 ins. dia., bears N.29°W., 22 lks. dist.,

marked  $\frac{1}{4}$  S B T.

51.50 Intersect W. bdy. of township at a point 18.20 chs. N.1° E. of the cor. to secs. 25 & 36, R. 8 W., and  
Set a post at point of intersection, 4 ft. long, 4 ins. square, 24 ins. in the ground, for closing cor. to secs. 30 & 31, marked C C T 20 S R 7 W on E., S 30 on N. face, S 31 on S. face, with 5 notches on N. & 1 notch on S. faces; from which

A fir, 12 ins. dia., bears N.20°E., 18 lks. dist.,  
marked T 20 S R 7 W S 30 B T.

A fir, 24 ins. dia., bears S.57°E., 25 lks. dist.,  
marked T 20 S R 7 W S 31 B T.

A fir, 18 ins. dia., bears N.82°W., 32 lks. dist.,  
marked T 20 S R 7 W C C S 30 & 31 B T.

A sandstone, 20x20 ins., in place marked W C, bears  
N.80°W., 6 lks. dist.

The N. & S. line is well blazed and diligent search was made for other lines, but none were found; therefore, the said N. & S. line having a divergence of 1°E. of a true N. & S. line, I rerun & reestablish the entire W. bdy. of the township, the notes of which I give in the exteriors of same.

Sept. 14, 1891.

N.0°4'W., on true line, bet. secs. 29 &amp; 30.

V.21°15'E.

4.00 Stream, 3 lks. wide, c N.60°E.  
13.70 A fir on line, 48 ins. dia., marked with 2 notches on N. & S. sides.  
17.75 Top of spur, c S.60°E. +450  
18.05 Fir, 40 ins. dia., on line, which I mark with 2 notches on N. & S. sides.  
27.00 Canyon, c E., rocky & precipitous. -150