

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS		
5.50	Yellow Creek, 5 lks. wide, c SE.	-75
13.00	Small spur, c SE.	+75
20.00	Canyon, c SE.	-75
30.25	Spur, c N.	+200
35.00	Canyon, c N.75°E.	-100
40.25	Set post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which An alder, 8 ins. dia., bears S., 31 lks. dist., marked $\frac{1}{4}$ S B T. (in gulch). A fir, 4 ins. dia., bears N.8°W., 8 lks. dist., marked $\frac{1}{4}$ S B T.	
57.50	Top of ridge, c NE.	+400
62.75	Divide, c N. & S.; descend. Enter green timber.	+25
70.75	Canyon, c N.30°W.; ascend.	-300
80.50	The cor. to secs. 19 & 20, 29 & 30.	+150
	Oct. 17, 1891.	
	S.89°45'W., on a true line, bet. secs. 19 & 30. Va.21°E.	
9.25	Stream, 2 lks. wide, c N.; ascend steep.	-250
26.75	Top of spur, c NE.	+700
34.50	Top of spur, c NW.	
40.00	Set sandstone, 12x10x5 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ on W. face; from which A fir, 50 ins. dia., bears S.26°W., 6 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 24 ins. dia., bears N.28°W., 42 lks. dist., marked $\frac{1}{4}$ S B T.	
50.20	Intersect W. bdy. of township at a point 19 chs. N.1°E. of old cor. to secs. 24 & 25, T. 20 S., R. 8 W., at which point of intersection I set a sandstone, 16x12x12 ins., 12 ins. in the ground, for closing cor. to secs. 19 & 30, marked C.C with 2 notches on S. & 4 notches on N. faces; from which	