

Subdivisions of T. 20 S., R. 7 W.

CHAINS

A fir, 40 ins. dia., bears N.23°E., 20 lks. dist.,
 marked T 20 S R 7 W S 19 B T.
 A fir, 30 ins. dia., bears S.47°E., 70 lks. dist.,
 marked T 20 S R 7 W S 30 B T.
 A maple, 5 ins. dia., bears N.40°W., 43 lks. dist.,
 marked T 20 S R 7 W C C S 19 & 30 B T.

Oct. 19, 1891.

N.0°4'W., on true line, bet. secs. 19 & 20.

Va.21°E.

Descend.

8.00	Canyon, c N.75°W.	-200
9.90	Canyon, c SW.	
19.00	Top of spur, c W.	+150
26.50	Canyon, c S.40°W.	-175
29.50	Top of spur, c SW.	+75
37.60	Top of spur, c W.	+200
40.00	Marked a fir, 40 ins. dia. with $\frac{1}{2}$ S on W. face, with 2 notches on N. & S. sides, for $\frac{1}{4}$ sec. cor., on line; from which	
	A fir, 30 ins. dia., bears N.45°W., 21 lks. dist., marked $\frac{1}{2}$ S B T.	
	A fir, 36 ins. dia., bears N.86°E., 32 lks. dist., marked $\frac{1}{4}$ S B T.	
53.35	Canyon, c S.61°W.	-175
56.75	Top of spur, c SW.	+75
62.50	Canyon, c SW.	-75
72.40	Top of ridge, c E. & W.	+300
80.00	Set a sandstone, 12x8x8, 8 ins. in the ground, for cor. to secs. 17, 18, 19 & 20, marked with 3 notches on S. & 5 notches on E. edges; from which	
	A maple, 15 ins. dia., bears N.26°E., 11 lks. dist., marked T 20 S R 7 W S 17 B T.	
	A fir, 36 ins. dia., bears S.52°E., 81 lks. dist., marked T 20 S R 7 W S 20 B T.	