

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

A fir, 36 ins. dia., bears S.26°W., 27 lks. dist.,
marked T 20 S R 7 W S 19 B T.

A maple, 20 ins. dia., bears N.20°W., 32 lks. dist.,
marked T 20 S R 7 W S 18 B T.

Oct. 19, 1891.

N.88°55'E., on a random line, bet. secs. 17 & 20.

Va.21°E.

40.00 Set temporary $\frac{1}{4}$ sec. cor.

80.60 Intersect N. & S. line, 35 lks. N. of cor. to secs. 16,
17, 20 & 21.

Thence I run

S.89°10'W., on a true line, bet. secs. 17 & 20.

Va.21°E.

8.73 Stream, 1 lk. wide, c N.80°W.

-100

20.00 Stream, 4 lks. wide, c SW.

-150

27.00 Top of spur, c S.; descend.

+100

31.75 Stream, 2 lks. wide, c S.40°E.

-100

40.30 Set post, 4 ft. long, 4 ins. square, 24 ins. in the
ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from
which

A fir, 50 ins. dia., bears N.44°W., 36 lks. dist.,
marked $\frac{1}{4}$ S B T.

A fir, 30 ins. dia., bears S.34°E., 29 lks. dist.,
marked $\frac{1}{4}$ S B T.

41.00 Spur, c S.30°E.

-15

54.75 Canyon, c SE.

-100

57.50 Spur, c SE.

+75

58.00 Canyon, c SE.

-50

65.50 Spur, c SE.

-300

70.00 Top of divide, c NE. & SW.; descend.

80.60 The cor. to secs. 17, 18, 19 & 20.

-200

Oct. 20, 1891.

S.89°45'W., on a true line, bet. secs. 18 & 19.