

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS			Va. 21° E.
1.50	Canyon, c N.		-150
6.00	Spur, c N.		+100
11.90	Canyon, c N.		-85
17.00	Spur, c N.		+125
24.75	Canyon, c N.		-80
30.50	Main spur, c NW.		+100
40.00	Set post, 4 ft. long, 4 ins. square, 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face; from which A dogwood, 4 ins. dia., bears N. 21° W., 9 lks. dist., marked $\frac{1}{4}$ S B T. A dogwood, 5 ins. dia., bears S. 80° E., 23 lks. dist., marked $\frac{1}{4}$ S B T.		-100
48.60	Intersect W. bdy. of the township at a point 18.40 chs. N. 1° E. of the old cor. to secs. 13 & 24; at this point of intersection I set a sandstone, 18x12x12 ins., 12 ins. in the ground, for closing cor. to secs. 18 & 19, marked C C with 3 notches on N. & S. faces; from which A fir, 36 ins. dia., bears N. 24° E., 5 lks. dist., marked T 20 S R 7 W S 18 B T. A fir, 24 ins. dia., bears S. 79° E., 39 lks. dist., marked T 20 S R 7 W S 19 B T. A maple, 16 ins. dia., bears S. 37° W., 10 lks. dist., marked T 20 S R 7 W C C S 18 & 19 B T. Oct. 20, 1891.		

N. 0° 4' W., bet. secs. 17 & 18.

		Va. 21° E.
1.75	Small canyon, c W.	-75
6.00	Stream, 2 lks. wide, c W.	
22.00	Spur, c NW.; descend.	+500
38.00	Stream, 3 lks. wide, c S. 80° W.	-500
40.00	Set V. maple post, 4 ft. long, 4 ins. square, 2 ft. in the ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which	