

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

on N. faces; from which

A fir, 24 ins. dia., bears N.66°E., 10 lks. dist.,
marked T 20 S R 7 W S 7 B T.

A yew, 7 ins. dia., bears S.47°E., 37 lks. dist.,
marked T 20 S R 7 W S 18 B T.

A dogwood, 7 ins. dia., bears S.87°W., 31 lks. dist.,
marked T 20 S R 7 W S 7 & 18 B T.

Oct. 23, 1891.

N.0°4'W., on a true line, bet. secs. 7 & 8.

Va.21°E.

.50 Stream, 7 lks. wide, c SW.

2.00 Ascend steep rocky brushy ridge on E. slope; cross
canyon.

38.00 Top of spur, c E. +300

40.00 Set sandstone, 24x12x7 ins., 18 ins. in the ground, for
 $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which

A V. maple, 5 ins. dia., bears N.60°E., 9 lks. dist.,
marked $\frac{1}{4}$ S B T.

A V. maple, 4 ins. dia., bears S.11°W., 10 lks. dist.,
marked $\frac{1}{4}$ S B T.

42.00 Canyon, c NE. -100

48.00 Spur, c N.50°E. +200

58.00 Stream, 2 lks. wide, c SE.; ascend. -200

80.00 Set sandstone, 18x12x10 ins., 12 ins. in the ground, for
cor. to secs. 5, 6, 7 & 8, marked with 5 notches on S.
and 5 notches on E. edges; from which

A fir, 14 ins. dia., bears S.84°E., 49 lks. dist.,
marked T 20 S R 7 W Sec 8 B T.

A maple, 7 ins. dia., bears N.66°E., 56 lks. dist.,
marked T 20 S R 7 W Sec 5 B T.

A fir, 24 ins. dia., bears S.45°W., 10 lks. dist.,
marked T 20 S R 7 W S 7 B T.

A maple, 6 ins. dia., bears N.62°W., 42 lks. dist.,
marked T 20 S R 7 W S 6 B T.

Oct. 24, 1891.

N. 89°30'E., on random line, bet. secs. 5 & 8.