

## County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 7 W.

CHAINS

notches on S. &amp; 1 notch on N. faces; from which

A fir, 14 ins. dia., bears N.13°W., 23 lks. dist.,  
marked T 20 S R 7 W C C S 6 & 7 B T.

A fir, 36 ins. dia., bears N.60°E., 55 lks. dist.,  
marked T 20 S R 7 W S 6 B T.

A fir, 30 ins. dia., bears S.15½°E., 77 lks. dist.,  
marked T 20 S R 7 W S 7 B T.

Oct. 25, 1891.

N.0°4'W., on true line, bet. secs. 5 &amp; 6.

Va.21°15'E.

6.00	Top of divide, c E. & W.	-100
11.00	Stream, 1 lk. wide, c W.	-100
32.00	Spur, c NW.; descend abrupt.	+100
40.00	Set sandstone, 12x12x7 ins., 10 ins. in the ground, for ¼ sec. cor., marked ¼ S on W. face; from which A fir, 30 ins. dia., bears S.47°W., 45 lks. dist., marked ¼ S B T. A fir, 40 ins. dia., bears S.89°E., 55 lks. dist., marked ¼ S B T.	-150
45.00	Stream, 2 lks. wide, c W.	-100
57.50	Bluff of rocks, 50 ft. high, c NW. & SE. Leave green timber.	
60.50	Top of spur, c N.20°W.; descend.	+200
72.00	Stream, 3 lks. wide, course NW.; ascend.	+400
89.00	Divide, c NW. & SE.; descend.	+300
97.00	Intersect N. bdy. of Twp., 9.20 chs. West of cor. to secs. 31 & 32, Twp. 19 S., and at point of intersection Set sandstone, 24x12x10 ins., 18 ins. in the ground, for closing cor. to secs. 5 & 6, marked C C with 5 notches on E. & 1 on W. faces; from which A fir, 36 ins. dia., bears S.78°E., 27 lks. dist., marked T 20 S R 7 W Sec. 5 B T. A fir, 14 ins. dia., bears S.61°W., 170 lks. dist., marked T 20 S R 7 W S 6 B T. A fir, 40 ins. dia., bears N.30°E., 98 lks. dist., marked T 20 S R 7 W C C S 5 & 6 B T.	

Oct. 26, 1891.