

## County Surveyor's Record, Douglas County, Oregon

North Bay. of T. 22 S., R. 7 W.

CHAINS

A cedar, 12 ins. dia., bears S.30°E., 28 lks. dist.  
 A cedar, 18 ins. dia., bears N.30°W., 55 lks. dist.  
 A cedar, 12 ins. dia., bears S.40°W., 50 lks. dist.

Subdivisions of T. 21 S., R. 7 W.  
 Survey by L. H. Wheeler under Contract No. 467 dated  
 April 7th, 1883.

Survey commenced June 16, 1883.

I commence at the cor. to secs. 1, 2, 35 & 36, on the south boundary of the township. I found but one witness tree standing. Reestablished the corner by setting a post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, marked T 21 S S 36 on NE., R 7 W S 1 on SE., T 22 S S 2 on SW. and S 35 on NW. face, with one notch on E. and 5 on W. edges; from which

Fir, 24 ins. dia., bears S.36°W., 32 lks. dist.,  
 marked T 22 S R 7 W S 2 B T.

Fir, 24 ins. dia., bears N.49°W., 72 lks. dist.,  
 marked T 21 S R 7 W S 35 B T.

Alder, 8 ins. dia., bears N.85°E., 28 lks. dist.,  
 marked T 21 S R 7 W S 36 B T.

Maple, 12 ins. dia., bears S.15°E., 20 lks. dist.,  
 marked T 22 S R 7 W S 1 B T.

North between secs. 35 &amp; 36.

V.20°E.

Along west slope of mountain.

15.00 Stream, 30 lks., flows SW.; along East slope.

40.00 Set a post, 4 ins. dia., 4 ft. long, with marked stone,  
 12 ins. in ground, marked  $\frac{1}{4}$  S on W. face; from which  
 A fir, 4 ins. dia., bears S.38°E., 27 lks. dist.,  
 marked  $\frac{1}{4}$  S B T.

A fir, 4 ins. dia., bears S.81°W.,  $4\frac{1}{8}$  lks. dist.,  
 marked  $\frac{1}{4}$  S B T.

75.00 Cross ridge, SW. &amp; NE.; thence along West slope.

80.00 Set a post, 6 ins. dia., 4 ft. long, with marked stone,  
 12 ins. in ground, for the cor. to secs. 25, 26, 35 &