

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	
	ins. in ground, for gr. sec. cor., marked $\frac{1}{2}$ S on W. face; from which Fir, 6 ins. dia., bears S.80°W., 25 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 5 ins. dia., bears N.83°E., 8 lks. dist., marked $\frac{1}{4}$ S B T.
47.50	Cross gulch, course West; thence along West slope.
80.00	A fir, 24 ins. dia., for cor. to secs. 23, 24, 25 & 26, marked T 21 S S 24 on NE., R 7 W S 25 on SE., S 26 on SW., S 23 on NW. face, with one notch on E. & 2 notches on S. edges; from which Fir, 50 ins. dia., bears N.45°E., 65 lks. dist., marked T 21 S R 7 W S 24 B T. Fir, 8 ins. dia., bears S.50°W., 97 lks. dist., marked T 21 S R 7 W S 26 B T. Fir, 14 ins. dia., bears N.40°W., 22 lks. dist., marked T 21 S R 7 W S 23 B T. Fir, 10 ins. dia., bears S.16°E., 47 lks. dist., marked T 21 S R 7 W S 25 B T. June 16, 1883.
	East, on random line, between secs. 24 & 25. V.20°E.
40.00	Set temp. gr. sec. cor.
79.60	Intersect Township line 54 lks. South of corner to secs. 19, 30, 25 & 24. Thence S.89°37'W., on true line, between secs. 24 & 25. Descend.
27.50	Cross branch, 5 lks. wide, flows South; ascend.
39.80	Set a post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which A fir, 20 ins. dia., bears N.80°E., 20 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 18 ins. dia., bears S.14°W., 32 lks. dist., marked $\frac{1}{4}$ S B T.