

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	
59.50	On top of hill; descend.
79.60	The cor. to secs. 23, 24, 25 & 26. July 21st, 1883.
	North between Secs. 23 & 24. V.20°E.
	Along West slope.
13.50	Cross branch, 2 lks., flows W.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Maple, 6 ins. dia., bears S.30°W., 35 lks. dist., marked $\frac{1}{4}$ S B T. Maple, 10 ins. dia., bears S.15°E., 40 lks. dist., marked $\frac{1}{4}$ S B T.
67.00	Cross branch, 4 lks., flows SW.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 13, 14, 23 & 24, marked T 21 S S 13 on NE., R 7 W S 24 on SE., S 23 on SW., S 14 on NW. face, with one notch on E. & 3 notches on S. edges; from which Fir, 8 ins. dia., bears S.25°E., 43 lks. dist., marked T 21 S R 7 W S 24 B T. Fir, 20 ins. dia., bears S.58°W., 34 lks. dist., marked T 21 S R 7 W S 23 B T. Fir, 12 ins. dia., bears N.45°E., 54 lks. dist., marked T 21 S R 7 W S 13 B T. Fir, 12 ins. dia., bears N.15°W., 31 lks. dist., marked T 21 S R 7 W S 14 B T.
	East, on random line, between secs. 13 & 24. V.21°E.
40.00	Set temp. gr. sec. cor.
79.67	Intersect East boundary, 45 lks. South of cor. to secs. 18, 19, 13 & 24.