

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	
	Thence S.89°41'W., on true line, between secs. 13 & 24. Along south slope.
17.00	Cross ridge, course N. & S.; descend.
39.84	Set post, 4 in. dia., 4 ft. long, with marked stone, 12 ins. in ground, for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on W. face; from which A fir, 8 ins. dia., bears S.18°E., 17 lks. dist., marked $\frac{1}{4}$ S B T. A fir, 12 ins. dia., bears N.27°W., 42 lks. dist., marked $\frac{1}{4}$ S B T.
48.50	Cross branch, 2 lks. wide, course south; thence along flat.
79.67	The cor. to secs. 13, 14, 23 & 24.
	North between secs. 13 & 14. Va.20 $\frac{1}{2}$ °E.
	Cross small flat.
7.00	Cross stream, 10 lks. wide, course SW.; along East slope.
40.00	Set stake, 5 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 8 ins. dia., bears S.85°E., 16 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 24 ins. dia., bears S.15°W., 8 lks. dist., marked $\frac{1}{4}$ S B T.
44.50	Cross gulch, course SE.; ascend.
63.00	On top ridge, course E. & W.; descend.
80.00	Set post, 5 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 11 & 12, 13 & 14, marked T 21 S S 12 on NE., R 7 W S 13 on SE., S 14 on SW., S 11 on NW. face, with one notch on E. & 4 notches on south edge; from which Fir, 20 ins. dia., bears S.68°E., 18 lks. dist., marked T 21 S R 7 W S 13 B T. Fir, 20 ins. dia., bears S.30°W., 17 lks. dist.,