

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS  
 55.00 Cross branch, 4 lks. wide, flows SE.; ascend.  
 70.50 Descend.  
 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 1, 2, 11 & 12, marked T 21 S S 1 on NE., R 7 W S 12 on SE., S 11 on SW., S 2 on NW. face, with 5 notches on S. and 1 on E. edges; from which

Fir, 16 ins. dia., bears N.11°E., 19 lks. dist., marked T 21 S R 7 W S 1 B T.

Fir, 16 ins. dia., bears S.52°E., 11 lks. dist., marked T 21 S R 7 W S 12 B T.

Fir, 16 ins. dia., bears S.56°W., 47 lks. dist., marked T 21 S R 7 W S 11 B T.

Fir, 10 ins. dia., bears N.33°W., 28 lks. dist., marked T 21 S R 7 W S 2 B T.

East, on random line, between secs. 1 & 12.

V.20°30'E.

40.00 Set temp.  $\frac{1}{4}$  sec. cor.  
 79.65 Intersect East boundary, 38 lks. South of cor. to secs. 6, 7, 1 & 12.  
 Thence S.89°44'West, on true line, bet. secs. 1 & 12.  
 Descend.  
 17.50 Creek, 15 lks. wide, flows North; ascend.  
 39.82 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{4}$  S on N. face; from which

Fir, 14 ins. dia., bears N.18°E., 25 lks. dist., marked  $\frac{1}{4}$  S B T.

Fir, 40 ins. dia., bears S.13°W., 80 lks. dist., marked  $\frac{1}{4}$  S B T.

47.00 Top of hill; thence along East slope.  
 79.65 The cor. to secs. 1, 2, 11 & 12.

June 18, 1883.