

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

face; from which

Fir, 40 ins. dia., bears West, 4 lks. dist., marked

 $\frac{1}{4}$ S B T.

Oak, 8 ins. dia., bears S.67°E., 75 lks. dist.,

marked $\frac{1}{4}$ S B T.

52.00 Creek, 15 lks. wide, flows SE.; ascend..

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 26, 27, 34 & 35, marked T 21 S S 26 on NE., R 7 W S 35 on SE., S 34 on SW., S 27 on NW. face, with 2 notches on E. and one notch on S. face; from which

Dogwood, 4 ins. dia., bears N.54°E., 28 lks. dist.,

marked T 21 S R 7 W S 26 B T.

Fir, 48 ins. dia., bears S.41°E., 57 lks. dist.,

marked T 21 S R 7 W S 35 B T.

Fir, 20 ins. dia., bears N.65°W., 35 lks. dist.,

marked T 21 S R 7 W S 27 B T.

Yew, 8 ins. dia., bears S.66°W., 32 lks. dist.,

marked T 21 S R 7 W S 34 B T.

East, on random line, between secs. 26 & 35.

V.19 $\frac{1}{2}$ °E.

40.00 Set temp. qr. sec. cor.

79.80 Intersect N. & S. line, 30 lks. South of cor. to secs. 25, 26, 35 & 36.

Thence S.89°47' West, on true line, between secs. 26 & 35. Descend.

34.50 Cross branch, 20 lks., flows South; ascend.

39.90 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

A fir, 4 ins. dia., bears N.22°E., 11 lks. dist.,

marked $\frac{1}{4}$ S B T.

A fir, 3 ins. dia., bears S.42°E., 32 lks. dist.,

marked $\frac{1}{4}$ S B T.