

## Subdivisions of T. 21 S., R. 7 W.

CHAINS

57.00

On top of hill; descend along south slope.

79.80

The cor. to secs. 26, 27, 34 &amp; 35.

June 20, 1883.

North between secs. 26 &amp; 27.

V.20°E.

Along flat.

40.00

Set a post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from which

Fir, 24 ins. dia., bears N.71°E., 62 lks. dist., marked  $\frac{1}{4}$  S B T.

Cedar, 60 ins. dia., bears West, 54 lks. dist., marked  $\frac{1}{4}$  S B T.

52.50

Cross ridge, course E. &amp; W.; descend.

79.75

Branch, 4 lks., flows N.80°E.

80.00

Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 22, 23, 26 & 27, marked T 21 S S 23 on NE., R 7 W S 26 on SE., S 27 on SW., S 22 on NW. faces, with 2 notches on S. & E. edges; from which

Cedar, 6 ins. dia., bears N.54°E., 25 lks. dist., marked T 21 S R 7 W Sec 23 B T.

Cedar, 10 ins. dia., bears S.80°E., 48 lks. dist., marked T 21 S R 7 W Sec 26 B T.

Fir, 60 ins. dia., bears N.45°W., 63 lks. dist., marked T 21 S R 7 W S 22 B T.

Maple, 6 ins. dia., bears S.44°W., 28 lks. dist., marked T 21 S R 7 W S 27 B T.

East, on random line, between secs. 23 &amp; 26.

V.20°E.

40.00

Set temp. gr. sec. cor.

79.70

Intersect N. & S. line, 45 lks. South of cor. to secs. 23, 24, 25 & 26.