

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Laurel, 12 ins. dia., bears S.45°W., 17 lks. dist.,
marked T 21 S R 7 W S 22 B T.

Fir, 20 ins. dia., bears S.67°E., 10 lks. dist.,
marked T 21 S R 7 W S 23 B T.

Fir, 20 ins. dia., bears N.25°W., 30 lks. dist.,
marked T 21 S R 7 W S 15 B T.

June 21, 1883.

East, on random line, between secs. 14 & 23.

V.21°E.

40.00 Set temp. qr. sec. cor.

79.84 Intersect N. & S. line, 48 lks. South of cor. to secs. 13,
14, 23 & 24.

Thence

S.89°39'W., on true line, between secs. 14 & 23.

Descend.

4.50 Creek, 10 lks. wide, flows South; ascend.

15.00 Cross spur, course S.20°E.

39.92 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which

Fir, 18 ins. dia., bears S.10°E., 17 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 8 ins. dia., bears N.58°W., 23 lks. dist.,
marked $\frac{1}{4}$ S B T.

51.00 On top of mountain; thence along south slope.

79.84 The cor. to secs. 14, 15, 22 & 23.

North between sections 14 & 15.

V.21°E.

Ascend.

20.50 On top of hill; descend.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which