

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

- Fir, 18 ins. dia., bears N.53°W., 35 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Fir, 24 ins. dia., bears S.45°E., 22 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 43.00 Branch, 2 lks., flows West; ascend.
- 67.00 Descend.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 10, 11, 14 & 15,
marked T 21 S S 11 on NE., R 7 W S 14 on SE., S 15 on
SW., S 10 on NW. faces, with 2 notches on E. & 4 on S.
edge; from which
- Fir, 18 ins. dia., bears N.70°W., 11 lks. dist.,
marked T 21 S R 7 W S 10 B T.
- Fir, 18 ins. dia., bears S.11°W., 11 lks. dist.,
marked T 21 S R 7 W S 15 B T.
- Fir, 12 ins. dia., bears N.72°E., 21 lks. dist.,
marked T 21 S R 7 W S 11 B T.
- Fir, 4 ins. dia., bears S.16°E., 95 lks. dist.,
marked T 21 S R 7 W S 14 B T.
-
- East, on random line, between secs. 11 & 14.
V.21 $\frac{1}{2}$ °E.
- 40.00 Set temp. qr. sec. cor.
- 79.75 Intersect N. & S. line, 60 lks. South of cor. to secs.
11, 12, 13 & 14.
- Thence
S.89°34'West, on true line, between secs. 11 & 14.
Along North slope of mountain.
- 39.87 A fir, 24 ins. dia. for qr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which
- Fir, 14 ins. dia., bears S.5°W., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.
- Fir, 20 ins. dia., bears N.25°E., 20 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 42.00 Cross spur, course N. & S.