

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS

79.75

The cor. to secs. 10, 11, 14 &amp; 15.

June 22, 1883.

North between secs. 10 &amp; 11.

V.21°E.

Along West slope of mountain.

40.00

Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on W. face; from whichFir, 24 ins. dia., bears N.14°E., 35 lks. dist.,  
marked  $\frac{1}{4}$  S B T.Fir, 36 ins. dia., bears S.74°E., 35 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

48.50

Cross spur, course SE. &amp; NW.; descend.

67.00

Creek, 8 lks. wide, flows West; ascend.

78.00

Creek, 4 lks. wide, flows SW.

80.00

Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 2, 3, 10 &amp; 11, marked T 21 S S 2 on NE., R 7 W S 11 on SE., S 10 on SW., S 3 on NW., with 2 notches on E. &amp; 5 on S. edges; from which

Fir, 40 ins. dia., bears N.51°E., 41 lks. dist.,  
marked T 21 S R 7 W S 2 B T.Fir, 40 ins. dia., bears S.21°E., 60 lks. dist.,  
marked T 21 S R 7 W S 11 B T.Maple, 12 ins. dia., bears S.65°W., 30 lks. dist.,  
marked T 21 S R 7 W S 10 B T.Fir, 40 ins. dia., bears N.50°W., 13 lks. dist.,  
marked T 21 S R 7 W S 3 B T.

East, on random line, between secs. 2 &amp; 11.

V.21 $\frac{1}{2}$ °E.

40.00

Set temp. qr. sec. cor.

79.60

Intersect N. & S. line, 46 lks. South of cor. to secs.  
1, 2, 11 & 12.