

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Thence

S.89°40' West, on true line, between secs. 2 & 11.

Along North slope of mountain.

19.00 Cross ridge, course NW. & SE.; along flat.

39.80 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from whichMaple, 4 ins. dia., bears N.26°E., 4 lks. dist., marked $\frac{1}{4}$ S B T.Fir, 18 ins. dia., bears S.67°W., 30 lks. dist., marked $\frac{1}{4}$ S B T.

77.75 Branch, 4 lks., flows South.

79.60 The cor. to secs. 2, 3, 10 & 11.

North, on random line, between secs. 2 & 3.

V.21 $\frac{1}{2}$ °E.

40.00 Set temp. gr. sec. cor.

98.40 Intersect North boundary of Town., 32 lks. East of cor. to Secs. 2 & 3.

Thence S.11'E., on true line, bet. secs. 2 & 3.

Ascend.

5.00 Top of hill; descend.

30.00 Branch, 2 lks., flows SE.; ascend.

58.40 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from whichHemlock, 12 ins. dia., bears S.25°E., 7 lks. dist., marked $\frac{1}{4}$ S B T.Hemlock, 5 ins. dia., bears N.71°W., 14 lks. dist., marked $\frac{1}{4}$ S B T.

66.30 On top; thence along flat.

98.40 The cor. to secs. 2, 3, 10 & 11.

June 23, 1883.

To find the cor. to secs. 33 & 34, 3 & 4, on S. bound. of