

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Fir, 16 ins. dia., bears S.30°E., 9 lks. dist.,
marked T 21 S R 7 W S 34 B T.

Fir, 18 ins. dia., bears S.35°W., 8 lks. dist.,
marked T 21 S R 7 W S 33 B T.

East, on random line, bet. secs. 27 & 34.

V.19 $\frac{1}{2}$ °E.

40.00 Set temp. gr. sec. cor.

80.27 Intersect N. & S. line, 36 lks. South of cor. to secs.
26, 27, 34 & 35.

Thence S.89°45'West, on true line, bet. secs. 27 & 34.

Along South slope.

.50 Branch, 2 lks., flows South.

25.00 Creek, 10 lks., flows South; ascend.

40.14 A fir, 3 ins. dia., for gr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which

Fir, 4 ins. dia., bears N.25°W., 4 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 4 ins. dia., bears S.44°E., 8 lks. dist.,
marked $\frac{1}{4}$ S B T.

80.27 The corner to secs. 27, 28, 33 & 34.

North between secs. 27 & 28.

V.20°E.

Along East slope of mountain.

35.00 Cross spur.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which

Hemlock, 12 ins. dia., bears S.78°E., 30 lks. dist.,
marked $\frac{1}{4}$ S B T.

Cedar, 12 ins. dia., bears N.68°W., 29 lks. dist.,
marked $\frac{1}{4}$ S B T.

48.50 Branch, 2 lks. wide, flows East.

78.50 Gulch.