

Subdivisions of T. 21 S., R. 7 W.

CHAINS
80.00

Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 21, 22, 27 & 28, marked T 21 S, S 22 on NE., R 7 W S 27 on SE., S 28 on SW., S 21 on NW. face, with 3 notches on E. & 2 notches on S. edges; from which

Fir, 40 ins. dia., bears N.80°E., 53 lks. dist., marked T 21 S R 7 W S 22 B T.

Fir, 40 ins. dia., bears S.10°W., 34 lks. dist., marked T 21 S R 7 W S 28 B T.

Fir, 40 ins. dia., bears N.52°W., 13 lks. dist., marked T 21 S R 7 W S 21 B T.

Dogwood, 12 ins. dia., bears S.73°E., 97 lks. dist., marked T 21 S R 7 W S 27 B T.

June 25, 1883.

East, on random line, between secs. 22 & 27.

V.20°E.

40.00 Set temp. qr. sec. cor.

80.20 Intersect N. & S. line, 40 lks. South of cor. to secs. 22, 23, 26 & 27.

Thence S.89°43'W., on true line, between secs. 22 & 27. Ascend.

20.00 Cross ridge, course NE.; thence along S. slope.

40.10 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

Fir, 36 ins. dia., bears N.78°W., 11 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 30 ins. dia., bears S.15°E., 14 lks. dist., marked $\frac{1}{4}$ S B T.

63.50 Branch, 6 lks. wide, flows South; ascend.

80.20 The cor. to secs. 21, 22, 27 & 28.

North between sections 21 & 22.

V.20°E.