

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS	Along East slope.
25.00	Cross ridge, E. & W.; descend.
40.00	Set post, 5 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 50 ins. dia., bears S.37°W., 21 lks. dist., marked $\frac{1}{4}$ S B T. Maple, 6 ins. dia., bears N.25°E., 16 lks. dist., marked $\frac{1}{4}$ S B T.
57.50	Cross spur, course NW.; descend.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 15, 16, 21 & 22, marked T 21 S S 15 on NE., R 7 W S 22 on SE., Sec 21 on SW., S 16 on NW. face, with 3 notches on S. & E. edges; from which Hemlock, 14 ins. dia., bears N.8°E., 21 lks. dist., marked T 21 S R 7 W S 15 B T. Hemlock, 12 ins. dia., bears N.25°W., 47 lks. dist., marked T 21 S R 7 W S 16 B T. Hemlock, 20 ins. dia., bears S.48°W., 39 lks. dist., marked T 21 S R 7 W S 21 B T. Fir, 30 ins. dia., bears S.18°E., 56 lks. dist., marked T 21 S R 7 W S 22 B T.
	East, on random line, between secs. 22 & 15. V.20 $\frac{1}{2}$ °E.
40.00	Set temp. qr. sec. cor.
80.47	Intersect N. & S. line, 33 lks. South of cor. to secs. 14, 15, 22 & 23. Thence S.89°46'West, on true line, between secs. 22 & 15. Along South slope.
26.00	Cross spur, course N. & S.; descend.
36.00	Branch, 2 lks. wide, course North. Thence along North slope.