

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Fir, 36 ins. dia., bears N.6°E., 27 lks. dist.,
marked T 21 S R 7 W S 10 B T.

Fir, 20 ins. dia., bears S.60°E., 27 lks. dist.,
marked T 21 S R 7 W S 15 B T.

Fir, 40 ins. dia., bears S.57°W., 27 lks. dist.,
marked T 21 S R 7 W S 16 B T.

Fir, 36 ins. dia., bears N.69°W., 44 lks. dist.,
marked T 21 S R 7 W S 9 B T.

Thence I run

North between secs. 9 & 10.

V.20°E.

Ascend slope 30°.

2.50 Top of spur, course E. & W.; descend 25°.

11.00 Cross gulch, course East.

Ascend 28°.

21.00 Descend 30°.

28.00 Ascend 20°.

35.00 Top of spur; descend 27°.

40.00 Set post, 4 x 4, by 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which

Hemlock, 10 ins. dia., bears N.81°E., 9 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 30 ins. dia., bears S.84°W., 21 lks. dist.,
marked $\frac{1}{4}$ S B T.

47.50 Ascend 32°.

62.50 Still ascend slope 24°.

69.50 Descend 27°.

76.50 Descend 21°.

80.00 Set a post, 6x6 ins. by 4 ft. long, with marked stone, 12
ins. in ground, for cor. to secs. 3, 4, 9 & 10, marked
T 21 S S 3 on NE., R 7 W S 10 on SE., S 9 on SW., S 4
on NW. face, with 3 notches on E. and 5 on S. edges;
from which

Fir, 36 ins. dia., bears N.70°E., 95 lks. dist.,