

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

marked T 21 S R 7 W S 3 B T.

Fir, 36 ins. dia., bears S.81°E., 64 lks. dist.,

marked T 21 S R 7 W S 10 B T.

Fir, 10 ins. dia., bears S.71°W., 40 lks. dist.,

marked T 21 S R 7 W S 9 B T.

Fir, 20 ins. dia., bears N.18°W., 107 lks. dist.,

marked T 21 S R 7 W S 4 B T.

East, on random line, between secs. 3 & 10.

V.21½°E.

40.00 Set temp. qr. sec. cor.

80.32 Intersect N. & S. line, 50 lks. South of post cor. to
secs. 2, 3, 10 & 11.

Thence I run

S.89°38'West, on true line, between secs. 3 & 10.

Along flat.

17.00 Cross branch, 10 lks. wide, flows NW.; ascend 18°.

29.00 On top of hill; descend 22°.

40.16 Set post, 4x4 ins. by 4-ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked ¼ S on N.
face; from whichFir, 36 ins. dia., bears N.16°E., 37 lks. dist.,
marked ¼ S B T.Maple, 6 ins. dia., bears S.40°E., 16 lks. dist.,
marked ¼ S B T.

44.50 Creek, 8 lks. wide, flows North; ascend +13°.

48.50 Descend 27°.

50.50 Branch, 3 lks. wide, flows S.85°E.; ascend 28°.

67.50 Slope 23°.

80.32 The cor. to secs. 3, 4, 9 & 10.

Sept 10th, 1884.

North, on random line, between secs. 3 & 4.

V.20½°E.

40.00 Set temp. qr. sec. cor.