

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	
	Ascend slope 13°.
34.00	Descend slope 36°.
40.00	Set post, 4x4 ins. by 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Cedar, 40 ins. dia., bears S.41°W., 13 lks. dist., marked $\frac{1}{4}$ S B T. Cedar, 36 ins. dia., bears S.12°E., 41 lks. dist., marked $\frac{1}{4}$ S B T.
40.50	Branch, 8 lks. wide, flows SE.; ascend 22°.
67.50	Slope 28°.
71.25	Slope 17°.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 28, 29, 32 & 33, marked T 21 S S 28 on NE., R 7 W S 33 on SE., S 32 on SW., S 29 on NW. face, with 4 notches on E. & 1 on S. edge; from which Fir, 30 ins. dia., bears N.61°W., 38 lks. dist., marked T 21 S R 7 W S 29 B T. Fir, 24 ins. dia., bears S.51°W., 33 lks. dist., marked T 21 S R 7 W S 32 B T. Fir, 20 ins. dia., bears S.56°E., 64 lks. dist., marked T 21 S R 7 W S 33 B T. Maple, 12 ins. dia., bears N.51°E., 56 lks. dist., marked T 21 S R 7 W S 28 B T.
	East, on random line, between secs. 28 & 33. V.20°E.
40.00	Set temp. gr. sec. cor.
80.50	Intersect N. & S. line, 44 lks. South of cor. to secs. 27, 28, 33 & 34. Thence I run S.89°41'West, on true line, between secs. 28 & 33. Ascend slope 29°.
7.00	Cross trail on top of ridge, course NW.; descend 36°.