

Subdivisions of T. 21 S., R. 7 W.

CHAINS

- 12.00 Slope 20°.
- 17.00 Slope 13°.
- 40.25 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which
- W. maple, 8 ins. dia., bears N.53°W., 5 lks. dist., marked $\frac{1}{4}$ S B T.
- Fir, 30 ins. dia., bears S.7°W., 53 lks. dist., marked $\frac{1}{4}$ S B T.
- 41.25 Branch, 2 lks. wide, flows South; ascend 27°.
- 60.00 Top of spur; descend 17°.
- 80.50 The cor. to secs. 28, 29, 32 & 33.
-
- North between secs. 28 & 29.
- V.20°E.
- Ascend slope 17°.
- 30.00 Top of mountain; descend 23°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which
- Fir, 30 ins. dia., bears S.66°E., 13 lks. dist., marked $\frac{1}{4}$ S B T.
- Fir, 20 ins. dia., bears S.65°W., 60 lks. dist., marked $\frac{1}{4}$ S B T.
- 49.00 Gulch, runs West; ascend slope 28°.
- 69.00 Descend 27°.
- 80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 20 & 21, marked T 21 S S 21 on NE., R 7 W S 28 on SE., S 29 on SW., S 20 on NW. face, with 4 notches on East and 2 on South edge; from which
- Fir, 24 ins. dia., bears N.48°E., 23 lks. dist., marked T 21 S R 7 W S 21 B T.
- Hemlock, 5 ins. dia., bears S.38°E., 8 lks. dist., marked T 21 S R 7 W S 28 B T.