

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS

Hemlock, 10 ins. dia., bears S.35°W., 26 lks. dist.,  
marked T 21 S R 7 W S 29 B T.

Hemlock, 8 ins. dia., bears N.46°W., 16 lks. dist.,  
marked T 21 S R 7 W S 20 B T.

East, on random line, between secs. 21 & 28.

V.20°E.

- 40.00 Set temp. qr. sec. cor.
- 80.35 Intersect N. & S. line, 15 lks. North of cor. to secs. 21,  
22, 27 & 28.
- Thence I run  
N.89°54'W., on true line, between secs. 21 & 28.  
Ascend slope 30°.
- 34.00 Cross trail on top of ridge, course NW.; descend 37°.
- 40.18 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N.  
face; from which
- Fir, 30 ins. dia., bears N.35°W., 36 lks. dist.,  
marked  $\frac{1}{4}$  S B T.
- Fir, 30 ins. dia., bears S.48°E., 12 lks. dist.,  
marked  $\frac{1}{4}$  S B T.
- 48.00 Ascend 17°.
- 67.00 Top of mountain; descend 29°.
- 74.00 Ascend 22°.
- 77.50 Slope 27°.
- 80.35 The cor. to secs. 20, 21, 28 & 29.  
Sept. 12th.

North between secs. 20 & 21.

V.21°E.

Descend slope 27°.

- 5.00 Gulch; ascend 18°.
- 21.50 Slope 22°.
- 35.00 Slope 16°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12