

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which

Fir, 24 ins. dia., bears S.30°W., 4 lks. dist., marked $\frac{1}{4}$ S B T.

Fir, 24 ins. dia., bears S.49°E., 61 lks. dist., marked $\frac{1}{4}$ S B T.

46.00 Descend 22°.

55.00 Descend 19°.

60.00 Descend 25°.

65.00 Creek, 20 lks. wide, flows W.; ascend 18°.

76.50 Slope 8°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 16, 17, 20 & 21, marked T 21 S S 16 on NE., R 7 W S 21 on SE., S 20 on SW., S 17 on NW. face, with 4 notches on E. & 3 on S. edges; from which

Fir, 40 ins. dia., bears N.47°W., 90 lks. dist., marked T 21 S R 7 W S 17 B T.

Fir, 30 ins. dia., bears S.22°W., 65 lks. dist., marked T 21 S R 7 W S 20 B T.

Fir, 30 ins. dia., bears S.60°E., 78 lks. dist., marked T 21 S R 7 W S 21 B T.

Fir, 36 ins. dia., bears N.61°E., 68 lks. dist., marked T 21 S R 7 W S 16 B T.

East, on random line, between secs. 16 & 21.

V.21°E.

40.00 Set temp. qr. sec. cor.

80.20 Intersect N. & S. line, 10 lks. North of cor. to secs. 15, 16, 21 & 22.

Thence I run

N.89°56' West, on true line, between secs. 16 & 21.

Descend slope 16°.

3.50 Cross creek, 10 lks. wide, flows S.80°W.; ascend 20°.

17.50 Descend 10°.