

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS 22.00	Creek, 3 lks. wide, flows South; ascend 10°.
29.00	Descend 12°. Trail, course N. & S.
35.00	Branch, 2 lks. wide, flows S.; ascend 18°.
40.10	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Fir, 40 ins. dia., bears N.64°E., 13 lks. dist., marked $\frac{1}{4}$ S B T. Hemlock, 5 ins. dia., bears S.10°W., 19 lks. dist., marked $\frac{1}{4}$ S B T. Along flat.
67.00	Descend 30°.
70.00	Branch, 6 lks. wide, flows South; ascend 37°.
74.00	Descend 12°.
80.20	The cor. to secs. 16, 17, 20 & 21.
<hr/> North between secs. 16 & 17. <div style="text-align: center;">V.21°E.</div> Ascend slope 8°.	
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for gr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 24 ins. dia., bears N.35°E., 18 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 16 ins. dia., bears S.40°W., 45 lks. dist., marked $\frac{1}{4}$ S B T.
43.00	On top of mountain; descend 15°.
79.25	Branch, 5 lks. wide, flows NE.; ascend 13°.
80.00	Set post, 5 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 8, 9, 16 & 17, marked T 21 S S 9 on NE., R 7 W S 16 on SE., S 17 on SW., S 8 on NW. faces, with 4 notches on East & South edges; from which Fir, 24 ins. dia., bears N.30°E., 78 lks. dist., marked T 21 S R 7 W S 9 B T..