

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Fir, 40 ins. dia., bears S.35°E., 8 lks. dist.,
marked T 21 S R 7 W S 16 B T.

Fir, 24 ins. dia., bears N.36°W., 36 lks. dist.,
marked T 21 S R 7 W S 8 B T.

Fir, 6 ins. dia., bears S.32°W., 95 lks. dist.,
marked T 21 S R 7 W S 17 B T.

Sept. 13, 1884.

East, on random line, between secs. 9 & 16.

V.21½°E.

40.00 Set temp. gr. sec. cor.

80.10 Intersect N. & S. line, 30 lks. North of cor. to secs. 9,
10, 15 & 16.

Thence

N.89°47'W., on true line, between secs. 9 & 16.

Ascend 22°.

17.00 Cross trail on top of ridge, bears N. & S.; descend 36°.

22.00 Descend 12°.

40.15 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for gr. sec. cor., marked ½ S on N.
face; from which

Fir, 40 ins. dia., bears N.45°W., 30 lks. dist.,
marked ½ S B T.

Fir, 40 ins. dia., bears S.44°E., 77 lks. dist.,
marked ½ S B T.

42.50 Gulch; ascend 18°.

62.00 Descend 22°.

78.00 Branch, 2 lks. wide, flows N.

80.10 The cor. to secs. 8, 9, 16 & 17.

North between sections 8 & 9.

V.21°E.

Ascend slope 13°.

10.00 Descend 10°.

39.75 Creek, 10 lks. wide, flows NW.; ascend 13°.