

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	
37.50	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Fir, 40 ins. dia., bears N.30°W., 33 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 36 ins. dia., bears S.10°E., 48 lks. dist., marked $\frac{1}{4}$ S B T.
53.50	Descend 18°.
67.50	Branch, 2 lks. wide, flows North; ascend slope 30°.
72.50	Slope 13°.
77.50	The cor. to secs. 29, 30, 31 & 32. Sept. 19, 1884.
<hr/>	
	North between secs. 29 & 30. V.20°E.
	Descend slope 12°.
9.00	Slope 30°.
37.00	Branch, 4 lks. wide, flows NW.; ascend 21°.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Cedar, 30 ins. dia., bears S.50°W., 33 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 40 ins. dia., bears N.10°E., 63 lks. dist., marked $\frac{1}{4}$ S B T.
41.50	Along flat.
67.50	Descend 27°.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 19, 20, 29 & 30, marked T 21 S S 20 on NE., R 7 W S 29 on SE., S 30 on SW., S 19 on NW. face, with 5 notches on E. & 2 on S. edges; from which Fir, 24 ins. dia., bears N.50°E., 77 lks. dist., marked T 21 S R 7 W S 20 B T. Fir, 30 ins. dia., bears N.13°W., 130 lks. dist.,