

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS

marked T 21 S R 7 W S 19 B T.

Fir, 40 ins. dia., bears S.3°E., 30 lks. dist.,

marked T 21 S R 7 W S 29 B T.

Fir, 40 ins. dia., bears S.40°W., 56 lks. dist.,

marked T 21 S R 7 W S 30 B T.

East, on random line, between secs. 20 &amp; 29.

V.20°E.

40.00 Set temp. qr. sec. cor.

80.20 Intersect N. & S. line, 50 lks. South of cor. to secs.  
20 & 21, 28 & 29.

Thence I run

S.89°39'W., on true line, between secs. 20 &amp; 29.

Ascend slope 27°.

10.00 Top of hill; descend slope 21°.

18.00 Ascend 18°.

27.00 Descend 15°.

35.00 Descend 29°.

40.10 A fir, 8 ins. dia., for qr. sec. cor., marked  $\frac{1}{4}$  S on N.  
face; from which

Fir, 18 ins. dia., bears N.30°E., 11 lks. dist.,

marked  $\frac{1}{4}$  S B T.

Fir, 30 ins. dia., bears S.5°E., 32 lks. dist.,

marked  $\frac{1}{4}$  S B T.

50.00 Gulch; ascend 26°.

70.50 Descend 27°.

80.20 The cor. to secs. 19, 20, 29 &amp; 30.

West, on random line, between secs. 19 &amp; 30.

V.20°E.

40.00 Set temp. qr. sec. cor.

76.75 Intersect west boundary of Town., 19 lks. North of cor.  
to secs. 24, 25, 19 & 30.

Thence I run

N.89°52'East, on true line, between secs. 19 &amp; 30.