

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS	Descend slope 27°.
3.00	Ascend slope 20°.
10.50	Descend 25°.
19.50	Branch, 2 lks. wide, flows S.; ascend 26°.
36.75	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which Fir, 10 ins. dia., bears N.20°E., 24 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 6 ins. dia., bears S.20°E., 18 lks. dist., marked $\frac{1}{4}$ S B T.
40.00	Descend slope 15°.
60.00	Ascend slope 19°.
76.75	The cor. to secs. 19, 20, 29 & 30.

North between secs. 19 & 20.

V.21°E.

	Ascend 27°.
12.50	Branch, 8 lks. wide, flows SW.; ascend 27°.
24.75	Descend 22°.
36.50	Branch, 3 lks. wide, flows W.; ascend 40°.
40.00	Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from which Fir, 40 ins. dia., bears N.78°W., 20 lks. dist., marked $\frac{1}{4}$ S B T. Fir, 20 ins. dia., bears N.35°E., 56 lks. dist., marked $\frac{1}{4}$ S B T.
71.00	Descend 28°.
80.00	Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 17, 18, 19 & 20, marked T 21 S S 17 on NE., R 7 W S 20 on SE., S 19 on SW., S 18 on NW. face, with 5 notches on E. & 3 in S. edge; from which Fir, 20 ins. dia., bears N.88°E., 62 lks. dist.,