

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

to secs. 13, 24, 18 & 19.

Thence I run

N.89°48'E., on true line, between secs. 18 & 19.

Descend 34°.

4.50 Branch, 4 lks. wide, flows NE.; ascend 30°.

20.00 Descend 30°.

35.90 Fir, 30 ins. dia., for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from whichFir, 24 ins. dia., bears N.5°E., 58 lks. dist., marked $\frac{1}{4}$ S B T.Fir, 14 ins. dia., bears N.70°W., 10 lks. dist., marked $\frac{1}{4}$ S B T.

45.00 Ascend 26°.

63.00 Descend 16°.

68.00 Ascend 16°.

70.50 Descend 11°.

75.90 The cor. to secs. 17, 18, 19 & 20.

North between secs. 17 & 18.

V.20°E.

Descend slope 28°.

11.50 Branch, 4 lks. wide, flows N.10°E.; ascend 18°.

20.50 Descend 18°.

37.00 Creek, 24 lks. wide, flows NW.; ascend 7°.

39.25 Branch, 4 lks. wide, flows SW.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W. face; from whichMaple, 24 ins. dia., bears S.64°W., 17 lks. dist., marked $\frac{1}{4}$ S B T.Fir, 24 ins. dia., bears N.53°E., 50 lks. dist., marked $\frac{1}{4}$ S B T.

77.50 Slope 27°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for cor. to secs. 7, 8, 17 & 18, marked