

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

T 21 S S 8 on NE., R 7 W S 17 on SE., S 18 on SW., S 7 on
on NW. face, with 5 notches on E. & 4 on S. edge; from
which

Fir, 8 ins. dia., bears N.19°W., 25 lks. dist.,
marked T 21 S R 7 W S 7 B T.

Oak, 5 ins. dia., bears N.33°E., 18 lks. dist.,
marked T 21 S R 7 W S 8 B T.

Oak, 7 ins. dia., bears S.67°E., 17 lks. dist.,
marked T 21 S R 7 W S 17 B T.

Oak, 5 ins. dia., bears S.10°W., 5 lks. dist.,
marked T 21 S R 7 W S 18 B T.

Sept. 21, 1884.

East, on random line, between secs. 8 & 17.

V.20°E.

40.00 Set temp. gr. sec. cor.

79.82 Intersect N. & S. line, 50 lks. South of cor. to secs. 8,
9, 16 & 17.

Thence I run

S.89°39' West, on true line, between secs. 8 & 17.

Ascend 25°.

12.00 Top; descend 30°.

17.00 Slope 35°.

31.50 Branch, 4 lks. wide, flows S.; ascend slope 35°.

39.91 Fir, 18 ins. dia., for $\frac{1}{4}$ sec. cor., marked $\frac{1}{4}$ S on N. face;
from which

Fir, 24 ins. dia., bears N.20°W., 30 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 20 ins. dia., bears South, 5 lks. dist., marked
 $\frac{1}{4}$ S B T.

45.00 Descend 27°.

57.00 Branch, 2 lks. wide, flows N.; ascend 26°.

69.00 Cross ridge, course NW.; descend 10°.

79.82 The cor. to secs. 7, 8, 17 & 18.

West, on random line, between secs. 7 & 18.

V.20°E.