

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 7 W.

CHAINS

- 40.00 Set temp. qr. sec. cor.
- 75.20 Intersect West boundary of Town., 29 lks.. North of cor.
to secs. 12, 13, 7 & 18.
- Thence I run
N.89°48'E., on true line, between secs. 7 & 18.
Ascend 30°.
- 8.50 Descend 14°.
- 32.00 Branch, 6 lks. wide, flows SE.; ascend 16°.
- 35.20 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N.
face; from which
Fir, 50 ins. dia., bears S.30°E., 23 lks. dist.,
marked $\frac{1}{4}$ S B T.
Cedar, 20 ins. dia., bears N.40°E., 42 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 37.50 Descend 12°.
- 45.00 Branch, 3 lks. wide, flows South; ascend 12°.
- 70.00 Slope 10°.
- 75.20 The cor. to secs. 7, 8, 17 & 18.
-
- North between secs. 7 & 8.
V.21°E.
- Ascend slope 27°.
- 7.50 Top of hill; descend 17°.
- 24.00 Branch, 3 lks. wide, flows East; ascend 22°.
- 32.00 Descend 17°.
- 40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12
ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on W.
face; from which
Fir, 30 ins. dia., bears S.35°E., 12 lks. dist.,
marked $\frac{1}{4}$ S B T.
Cedar, 20 ins. dia.; bears S.86°W., 44 lks. dist.,
marked $\frac{1}{4}$ S B T.
- 41.00 Branch, 2 lks. wide, flows E.; ascend 10°.
- 50.00 Descend slope 12°.