

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 21 S., R. 7 W.

CHAINS

West, on random line, between secs. 6 &amp; 7.

V.20°E.

40.00 Set temp. qr. sec. cor.

74.80 Intersect West boundary of Town., 34 lks. North of cor.  
to secs. 1, 12, 6 & 7.

Thence I run

N.89°45'East, on true line, between secs. 6 &amp; 7.

Ascend 7°.

15.00 Descend 18%.

27.00 Ascend 38°.

34.80 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on N.  
face; from whichFir, 20 ins. dia., bears N.65°W., 22 lks. dist.,  
marked  $\frac{1}{4}$  S B T.Fir, 20 ins. dia., bears S.33°W., 57 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

36.00 Descend 30°.

47.00 Ascend 18°.

59.50 Descend 15°.

68.50 Slope 20°.

74.80 The cor. to secs. 5, 6, 7 &amp; 8.

North, on random line, between secs. 5 &amp; 6.

V.21°E.

40.00 Set temp. qr. sec. cor.

99.20 Intersect North boundary of Town., 42 lks. West of cor.  
to secs. 5 & 6.

Thence I run

S.18°W., on true line, between secs. 5 &amp; 6.

Ascend slope 10°.

21.20 Cross ridge, course E. &amp; W.; descend 15°.

59.20 Set post, 4 ins. dia., 4 ft. long, with marked stone, 12  
ins. in ground, for qr. sec. cor., marked  $\frac{1}{4}$  S on W.  
face; from which