

Subdivisions of T. 21 S., R. 7 W.

CHAINS

Fir, 12 ins. dia., bears N.80°W., 9 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

Fir, 14 ins. dia., bears S.80°E., 10 lks. dist.,  
marked  $\frac{1}{4}$  S B T.

68.00 Along bottom.

79.00 Smith River, 105 lks. wide, flows W.; ascend 37°.

99.20 The cor. to secs. 5, 6, 7 & 8.

Sept. 24, 1884.

West Bdy. of T. 20 S., R. 5 W., W.M., Ore.  
Survey by Harvey Gordon under Contract No. 49 dated  
Oct. 17th, 1854.

South on W. boundary of Sec. 19.

\* \* \* \* \*

80.00 Set post corner of secs. 19, 24, 25 & 30; from which

A R. fir, 24 ins. dia., bears N.49°E., 44 lks. dist.

A R. fir, 12 ins. dia., bears S.65°E., 76 lks. dist.

A R. fir, 50 ins. dia., bears N.72°W., 27 lks. dist.

A redwood, 18 ins. dia., bears S.70°W., 42 lks. dist.

Dec. 22nd, 1854.

South on W. boundary of Sec. 30.

Var. 19°30'E.

29.20 Stream, 3 lks. wide, course SE. -40

40.00 Set quar. sec. post; from which +75

A R. fir, 14 ins. dia., bears N.35°W., 13 lks. dist.

A R. fir, 15 ins. dia., bears S.62°E., 14 lks. dist.

52.00 Summit ridge of the Calapooia Mountains, course SE. +20

59.60 Stream, 2 lks. wide, course SW. -75

63.00 Top of hill. +100

73.20 Stream, 2 lks. wide, course W. -150

80.00 Set post corner of secs. 25, 30, 31 & 36; from which +500

A R. fir, 9 in. dia., bears S.10°W., 11 lks. dist.

A R. fir, 20 in. dia., bears S.17°E., 8 lks. dist.

A R. fir, 9 in. dia., bears N.58°E., 31 lks. dist.

A R. fir, 40 in. dia., bears N.3°W., 65 lks. dist.