

## County Surveyor's Record, Douglas County, Oregon

West Bdy. of T. 20 S., R. 5 W.

CHAINS

	South on W. boundary of Sec. 31.	
		Var. 19°30'
1.00	Top of hill; begin to descend.	+3
9.16	Stream, 1 lk. wide, course W.	-50
20.60	Stream, 1 lk. wide, course W.	
37.00	Top of ridge, course SW.	+150
40.00	Set quar. sec. post; from which	-10
	A R. fir, 30 ins. dia., bears N.61°W., 25 lks. dist.	
	A R. fir, 15 ins. dia., bears N.23°E., 29 lks. dist.	
	A mountain peak, said to be near the right bank of Siuslaw Creek, bears N.64°57'W., 20.95 miles dist.	
	A 2nd peak bears N.66°21'W., 21.40 miles dist.	
72.90	Stream, 1 lk. wide, course E.	-75
80.00	Set post corner of Townships 20 & 21 South of Ranges 5 and 6 West; from which	+5
	A R. fir, 20 ins. dia., bears N.87°W., 120 lks. dist.	
	A R. fir, 20 ins. dia., bears S.82°W., 89 lks. dist.	
	A R. fir, 15 ins. dia., bears S.28°E., 73 lks. dist.	
	A redwood, 30 ins. dia., bears N.36°E., 105 lks. dist.	

South Bdy. of T. 20 S., R. 6 W.  
Survey by J. H. McClung under Contract No. 173 dated  
July 20th, 1872.

	Beginning at the established corner to Townships 20 & 21 South, Ranges 5 & 6 West, I ran	
	West, on south boundary of Section 36, T. 20 S., R. 6 W.	
		Va. 19°30'E.
31.25	A fir, 26 ins. dia.	
40.00	Set post for $\frac{1}{2}$ sec. corner; from which	
	A chinquapin, 5 in. dia., bears S.66 $\frac{1}{2}$ °E., 16 lks.	
	A chinquapin, 5 in. dia., bears N.81°W., 20 lks.	
80.00	Set post for corner to secs. 1, 2, 35 & 36, on hillside facing North; from which	
	A fir, 24 in. dia., bears S.45°E., 38 lks. dist.	
	A fir, 5 ins. dia., bears N.17 $\frac{1}{2}$ °E., 25 lks. dist.	
	A laurel, 4 ins. dia., bears N.45°W., 20 lks. dist.	