

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 20 S., R. 6 W.

CHAINS

A fir, 48 ins. dia., bears N.71°E., 32 lks. dist.
 A fir, 14 in. dia., bears N.62½°W., 23 lks. dist.
 A cedar, 6 ins. dia., bears S.47°W., 25 lks. dist.

West, between secs. 4 & 33.

Va. 19°35'E.

15.00 Leave river bottom, NW. & SE.

40.00 Set post for ¼ sec. corner; from which

A fir, 10 ins. dia., bears S.59°E., 40 lks.

A wh. willow, 4 ins. dia., bears S.62½°W., 12 lks.

55.00 Enter river bottom, e E. & W.

60.00 Smith River, 50 lks. wide, runs NW.

80.00 Set post for cor. to secs. 4, 5, 32 & 33, on top of spur,
 e N. & S. There being no tree convenient, deposited
 stone, 9x8x5 marked with "x".

West, between secs. 5 & 32.

Va. 19°45'E.

19.75 Brook, 3 lks. wide, runs N.

30.50 Enter S. River, running SW.

32.50 Leave same, running NW.

40.00 Set sandstone, 3x2x2 feet, on side of high stony point
 bearing NW. & SW., for ¼ sec. corner; from which

A maple, 7 ins. dia., bears N.1°E., 50 lks. dist.

80.00 Set post for cor. to secs. 5, 6, 31 & 32; from which

A fir, 14 in. dia., bears S.65°E., 18 lks. dist.

A hemlock, 12 ins. dia., bears N.2°E., 65 lks. dist.

A maple, 5 ins. dia., bears S.2½°W., 25 lks. dist.

A dogwood, 6 ins. dia., bears N.53°W., 40 lks. dist.

Aug. 9, 1872.

West, between secs. 6 & 31.

Va. 18°45'E.

5.00 Enter Smiths River bottom, E. & W.

13.50 Smith River, 40 lks. wide, runs S.35°W.