

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 6 W.

CHAINS		
	S.89°24'W., on true line.	
29.55	Foot of hill, course N. & SW.	-100
37.50	Enter creek, 12 lks. wide, runs W.	
39.00	Leave same, runs S.70°W.	
39.78	Set $\frac{1}{4}$ sec. post; from which	
	An alder, 6 ins. dia., bears S.81°W., 20 lks.	
	An alder, 5 ins. dia., bears S.59°E., 21 lks.	
79.55	The cor. to secs. 25, 26, 35 & 36.	
<hr/>		
	North bet. secs. 25 & 26.	
	Va.19°30'E.	
12.50	A red fir, 60 ins. dia.	
20.00	Leave green timber, NE. & SW.	
22.50	Summit of ridge, NE. & SW.	+100
40.00	Set sandstone, 12x10x8 ins., for $\frac{1}{4}$ sec. cor.	+75
62.50	Brook, 5 lks. wide, runs NW.	
80.00	Set sandstone, 16x10x6, for cor. to secs. 23, 24, 25 & 26;	
	from which	
	A laurel, 6 in. dia., bears S.70°W., 10 lks.	
<hr/>		
	East, on random, bet. secs. 24 & 25.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
80.00	Intersect East boundary of Town., 60 lks. South of cor.	
	to secs. 24 and 25.	
	S.89°34'W., on true line.	
40.00	Set post for $\frac{1}{4}$ sec. cor. in edge of green timber, course	
	NE. & SW.; from which	
	A maple, 7 ins. dia., bears S.35 $\frac{1}{2}$ °W., 40 lks.	
	A laurel, 4 ins. dia., bears S.55°E., 15 lks.	
80.00	The corner to secs. 23, 24, 25 & 26.	
	Thurs., Aug. 15, 1872.	
<hr/>		
	North between secs. 34 & 35.	
2.50	Smith River, 30 lks. wide, c W.	
40.00	Set post for $\frac{1}{4}$ sec. corner; from which	+50