

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 6 W.

CHAINS		
	A fir, 6 ins. dia., bears N.67°E., 25 lks. A fir, 5 ins. dia., bears S.53°W., 16 lks.	
80.00	Set post for corner to secs. 26, 27, 34 & 35; from which A fir stub, 40 in. dia., bears N.59°E., 20 lks. A fir stub, 40 ins. dia., bears N.30°W., 4 lks. A fir, 6 ins. dia., bears S.80°E., 25 lks. A laurel, 4 ins. dia., bears S.14°W., 19 lks.	+100
<hr/>		
	East, on random, bet. secs. 26 & 35.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
80.45	Intersect N. & S. line, 75 lks. N. of cor. to secs. 25, 26, 35 & 36. N.89°28'W., on true line.	
40.22	Set post for $\frac{1}{4}$ sec. cor.; from which A fir stub, 40 in. dia., brs. N.20°W., 14 lks. A laurel, 6 in. dia., bears S.8°W., 19 lks.	
80.45	The cor. to secs. 26, 27, 34 & 35.	
<hr/>		
	North between secs. 26 & 27. Va.19°30'E.	
40.00	Set post for $\frac{1}{4}$ sec. cor. A fir, 48 ins. dia., bears S.64°E., 25 lks. A laurel, 6 ins. dia., bears S.55°W., 4 lks.	
61.50	A fir, 48 ins. dia.	
80.00	Set post for cor. to secs. 22, 23, 26 & 27, on top of ridge, brs. N. & S.; from which A laurel, .6 in. dia., S.10°E., 15 lks. A laurel, 6 in. dia., S.47°W., 45 lks. A laurel, 4 in. dia., N.39°W., 11 lks. A fir, 5 in. dia., N.6 $\frac{1}{2}$ °E., 40 lks.	+100
<hr/>		
	East, on random, bet. secs. 23 & 26.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
80.16	Intersect N. & S. line at corner.	