

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 20 S., R. 6 W.

CHAINS		
	West on true line.	
11.25	Stream, 10 lks. wide, course N.	-75
35.00	Summit of ridge, brs. N. & S.	+100
40.08	Marked stone in place on west slope of ridge, for $\frac{1}{2}$ sec. cor.	-50
41.50	Canyon, course N.	-50
52.50	Summit of ridge, c N. & S.	+150
66.00	Canyon, course N.	-150
80.16	The corner to secs. 22, 23, 26 & 27.	+150
	Aug. 21, 1872.	
<hr/>		
	North between secs. 33 & 34.	
5.00	Leave creek bottom, E. & W.	
40.00	Set post for $\frac{1}{4}$ sec. corner; from which	+60
	A fir, 5 in. dia., bears N.52°W., 40 lks. dist.	
	A fir, 5 in. dia., bears S.37 $\frac{1}{2}$ °E., 30 lks. dist.	
80.00	Set post for cor. to secs. 27, 28, 33 & 34; from which	
	A fir stub, 60 in. dia., S.72°W., 20 lks. dist.	
	A fir stub, 12 in. dia., N.30°E., 25 lks. dist.	
	A fir, 3 in. dia., bears S.76°E., 21 lks. dist.	
	A fir, 6 in. dia., bears N.23°W., 119 lks. dist.	
<hr/>		
	East, on rand., bet. secs. 27 & 34.	
40.00	Set temporary $\frac{1}{4}$ sec. cor.	
80.40	Intersect N. & S. line, 21 lks. N. of corner.	
	N.89°51'W., on true line.	
40.20	Set post and deposited stone, 3x3x2 in., marked "x", there being no trees convenient.	-50
80.40	The corner to secs. 27, 28, 33 & 34.	-75
<hr/>		
	North between secs. 27 & 28.	
	Va.19°40'E.	
40.00	Set post for $\frac{1}{2}$ sec. cor.; from which	
	A fir, 6 in. dia., S.66°W., 35 lks.	
	A fir, 5 in. dia., N.10°E., 10 lks.	