

County Surveyor's Record, Douglas County, Oregon

North Bdy. of T. 22 S., R. 6 W.

CHAINS
40.00

Set gr. sec. post; from which.

A fir, 30 in. dia., bears N.45°W., 24 lks. dist.

A fir, 24 ins. dia., bears S.27°E., 20 lks. dist.

62.50 Top of ridge, course North.

80.00 Set post corner of secs. 5, 6, 31 & 32; from which

A hemlock, 24 in. diam., bears N.30°W., 22 lks. dist.

A fir, 84 ins. diam., bears N.55°E., 18 lks. dist.

A fir, 40 ins. diam., bears S.32°E., 50 lks. dist.

A fir, 48 ins. diam., bears S.72°W., 45 lks. dist.

West on North boundary of Sec. 6.

Var. 19°45'E.

1.25 Stream, 3 lks. wide, course SE.

13.00 Top of ridge, course NE.

32.40 Stream, 1 lk. wide, course SW.

40.00 Set gr. sec. post; from which

A fir, 12 ins. diam., bears S.38°W., 10 lks. dist.

A fir, 12 in. diam., bears N.35°E., 45 lks. dist.

59.00 Stream, 3 lks. wide, course NW.

70.00 Top of ridge, course NW.

80.00 Set post cor. of Townships 21 & 22 S., Ranges 6 & 7 West;
from which

A fir, 18 ins. diam., bears N.59°E., 57 lks. dist.

A fir, 24 ins. diam., bears S.28°E., 13 lks. dist.

A cedar, 10 ins. dia., bears S.68°W., 9 lks. dist.

A fir, 20 in. dia., bears N.32°W., 104 lks. dist.

Subdivisions of T. 21 S., R. 6 W.
Survey by W. H. Byars under Contract No. 152 dated
June 3rd, 1871.

Subdivision commenced September 8th, 1871.

From the corner to Sections 1, 2, 35 and 36, on the south

boundary of the township, I ran

North between sections 35 and 36.

Variation by solar compass 20°E.

40.00 Set $\frac{1}{2}$ sec. post; from which

+100