

## County Surveyor's Record, Douglas County, Oregon

East Bdy. of T. 21 S., R. 6 W.

CHAINS  
 48.75 Branch, 15 lks. wide, flows NW.; along flat.  
 61.50 Ascend 10°.  
 72.00 Descend 18°  
 80.00 Found post gone, trees gone. Reestablished cor. to secs. 1, 12, 6 & 7 by setting post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, marked T 21 S S 6 on NE., R 5 W S 7 on SE., R 6 W S 12 on SW., S 1 on NW. face, with 5 notches on S. and 1 on North edge; from which

Fir, 14 ins. dia., bears N.57°E., 27 lks. dist., marked T 21 S R 5 W S 6 B T.

Fir, 14 ins. dia., bears S.60°E., 24 lks. dist., marked T 21 S R 5 W S 7 B T.

Fir, 10 ins. dia., bears S.42°W., 20 lks. dist., marked T 21 S R 6 W S 12 B T.

Fir, 20 ins. dia., bears N.22°W., 17 lks. dist., marked T 21 S R 6 W S 1 B T.

Sept. 26th, 1884.

South Bdy. of T. 21 S., R. 6 W.  
 Survey by Wm. P. Wright under Contract No. 514 dated August 27th, 1884.

Start from the cor. to secs. 2, 3, 34 & 35. Found the post gone and only one bearing tree standing. Reestablished the same by setting post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, marked T 21 S S 35 on NE., R 6 W S 2 on SE., T 22 S S 3 on SW., S 34 on NW. face, with two notches on E. & 4 on W. edges; from which

Fir, 24 ins. dia., bears S.70°W., 34 lks. dist., marked T 22 S R 6 W S 3 B T.

Oak, 14 ins. dia., bears N.14°W., 61 lks. dist., marked T 21 S R 6 W S 34 B T.

Fir, 14 ins. dia., bears S.2°E., 56 lks. dist., marked T 22 S R 6 W S 2 B T.

Fir, 6 ins. dia., bears N.58°E., 98 lks. dist.,