

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 21 S., R. 6 W.

CHAINS

marked T 21 S R 6 W S 35 B T.

West, on South boundary between secs. 3 and 34.

V.21°E.

Descend slope 12°.

10.55 Branch, 5 lks. wide, flows S.; ascend 10°.

35.00 Enter timber.

40.10 To place where old gr. sec. cor. stood; trees still standing. Reestablished the same by setting post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, marked $\frac{1}{4}$ S on N. face; from which

Fir, 30 ins. dia., bears N.13°W., 21 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 30 ins. dia., bears S.71°W., 23 lks. dist.,
marked $\frac{1}{4}$ S B T.

51.50 Top of ridge, bears N. & S.; descend 20°.

80.19 To place where old cor. to secs. 33, 34, 3 & 4 stood. One of the bearing trees standing. Reestablished the cor. by setting post, 6 ins. dia., 4 ft. long, in ground 12 ins., with marked stone, marked T 21 S S 34 on NE., R 6 W S 3 on SE., T 22 S S 4 on SW., S 33 on NW. face, with 3 notches in E. & W. edges; from which

Fir, 30 ins. dia., bears N.73°E., 36 lks. dist.,
marked T 21 S R 6 W S 34 B T.

Fir, 10 ins. dia., bears S.20°E., 60 lks. dist.,
marked T 22 S R 6 W S 3 B T.

Fir, 10 ins. dia., bears S.40°W., 50 lks. dist.,
marked T 22 S R 6 W S 4 B T.

Fir, 10 ins. dia., bears N.35°W., 70 lks. dist.,
marked T 21 S R 6 W S 33 B T.

West, on south boundary between secs. 33 and 4.

V.20 $\frac{1}{2}$ °E.

Descend slope 20°.

19.40 Cross branch, 6 lks. wide, flows South; ascend 35°.

24.50 Cross spur, course N. & S.; descend 21°.