

County Surveyor's Record, Douglas County, Oregon

South Bdy. of T. 21 S., R. 6 W.

CHAINS

40.00

Could find no trace of qr. sec. cor. or bearing trees.
Set post, 4 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, for qr. sec. cor., marked $\frac{1}{4}$ S on N. face; from which

Maple, 8 ins. dia., bears N.64°W., 38 lks. dist.,
marked $\frac{1}{4}$ S B T.

Fir, 6 ins. dia., bears S.26°E., 46 lks. dist.,
marked $\frac{1}{4}$ S B T.

43.75 Cross gulch South; ascend 35°.

52.75 Cross ridge, NE. & SW.; descend 17°

60.50 Slope 24°.

71.50 Slope 18°.

79.90 To where the cor. to secs. 4, 5, 32 & 33 stood. Post gone, bearing trees all gone, but one, that down. Re-established the cor. by setting post, 6 ins. dia., 4 ft. long, with marked stone, 12 ins. in ground, marked T 21 S S 33 on NE., R 6 W S 4 on SE., T 22 S S 5 on SW., S 32 on NW. face, with two notches on W. and 4 on E. edge; from which

Fir, 32 ins. dia., bears N.52°E., 47 lks. dist.,
marked T 21 S R 6 W S 33 B T.

Fir, 36 ins. dia., bears S.50°E., 27 lks. dist.,
marked T 22 S R 6 W S 4 B T.

Fir, 30 ins. dia., bears S.17°W., 44 lks. dist.,
marked T 22 S R 6 W S 5 B T.

Fir, 24 ins. dia., bears N.52°W., 60 lks. dist.,
marked T 21 S R 6 W S 32 B T.

West, on south boundary between secs. 5 & 32.

V.20 $\frac{1}{2}$ °E.

Descend slope 18°.

6.40 Branch, 4 lks. wide, flows SW.; ascend 20°.

28.00 Cross spur; descend 24°.

40.00 Found qr. sec. cor. gone. Reestablished the same by setting post, 4 ins. dia., 4 ft. long, with marked