

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 21 S., R. 6 W.

CHAINS

NE., R 6 W S 25 on SE., S 26 on SW., S 23 on NW. face;
from which

Fir, 30 ins. dia., bears S.68°W., 41 lks. dist.,
marked T 21 S R 6 W S 26 B T.

Cedar, 30 ins. dia., bears S.32°E., 25 lks. dist.,
marked T 21 S R 6 W S 25 B T.

Cedar, 30 ins. dia., bears N.50°E., 17 lks. dist.,
marked T 21 S R 6 W S 24 B T.

Cedar, 36 ins. dia., bears N.42°W., 64 lks. dist.,
marked T 21 S R 6 W S 23 B T.

Note: all slopes as given by me in the field notes of
this township have been corrected and the corners lo-
cated according to the distance thus obtained.

North between secs. 23 & 24.

V.20½°E.

Ascend slope 15°.

22.00 Cross ridge, E. & W.; descend 12°.

40.00 Set post, 4 ins. dia., 4 ft. long, with marked stone,
12 ins. in ground, for qr. sec. cor., marked ¼ S on W.
face; from which

Fir, 12 ins. dia., bears S.47°E., 18 lks. dist.,
marked ¼ S B T.

Fir, 36 ins. dia., bears S.87°W., 30 lks. dist.,
marked ¼ S B T.

45.50 Cross branch, 5 lks. wide, flows East; ascend 40°.

50.00 Slope 16°.

75.00 Descend 15°.

80.00 Set post, 6 ins. dia., 4 ft. long, with marked stone,
12 ins. in ground, for cor. to secs. 13, 14, 23 & 24,
marked T 21 S S 13 on NE., R 6 W S 24 on SE., S 23 on
SW., S 14 on NW. face, with 3 notches on S. and 1 on
E. edge; from which

Fir, 16 ins. dia., bears N.80°E., 60 lks. dist.,
marked T 21 S R 6 W S 13 B T.

Hemlock, 12 ins. dia., bears S.80°E., 64 lks. dist.,